ESLINGA POSICIONAMIENTO EXA22

WORK POSITIONING SYSTEMS

Fall protection



Certifications and norms



ANSI Z359.3-2019

Specific benefits



Hygiene

· Harnesses and textiles can be washed with neutral soap



Performance

· Strap with improved abrasion resistance and certified for use on sharp edges



Easy to use

- · Automatic loops optimizing installation and locking safety
- · NFC system guarantees traceability



Durability

· High webbing tenacity thanks to its weave and width



Compatibility

· Compatible with all kind of harnesses

Applications

- Building
- Heavy industry
- Light industry
- Maintenance
- Automotive
- Oil & Gas (extraction)





ESLINGA POSICIONAMIENTO EXA22

WORK POSITIONING SYSTEMS

Fall protection

Standards - Details

Technical details

Type of equipment	Flat sling
Composition of the main support	Polyester
Max. length	1,8
Min. length	1,3
Adjustment	Adjustment loop
With connector	yes
Included elements	Storage bag
Color	Black-Yellow
Connector (user side)	Automatic lock hook, steel, opening 20mm
SIZE	1,3 to 1,8 m
Connector (structure side)	Self-locking hook, steel, opening 20 mm







ESLINGA POSICIONAMIENTO EXA22

WORK POSITIONING SYSTEMS

Fall protection

Logistics information										
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight		
WCOEXA22	Black-Yellow	1,3 to 1,8 m	ESLINGA POSICIONAMIENT O EXA22	0	0	10	1	0.0		



